

ViewSonic® PROJECTOR **PG700WU**

Key Features

Bright Images in Any Environment |
WUXGA resolution for Subtle Details |
Amazing Color Accuracy | Immersive 3D
Experience | More Connectivity



Product Description

The ViewSonic PG700WU is a high brightness WUXGA projector with 1920 x 1200 resolution, and a 16:10 aspect ratio. 3500 ANSI lumens of brightness allow PG700WU to project images full of depth and detail, even in brightly lit spaces, such as meeting rooms and classrooms. Dual HDMI inputs ports allow you to flexibly connect your laptop, PC and other high definition devices for presentation files and multimedia. With the USB Type A with power supply, it can connect with wireless HDMI dongle for wireless presentation. In addition, utilizing PG700WU's SuperEco mode extends the projector's lamp life to up to 15,000 hours, effectively reducing lamp replacement and maintenance costs.

Visit Us ■ www.viewsonic.com

SPECIFICATION

Projection system:	0.48" WUXGA
Native Resolution:	1920x1200
DC type:	DC3
Brightness:	3500 ANSI Lumens
Contrast Ratio with SuperEco mode:	12000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/15000
Lamp Watt:	203W
Lens:	F=2.0~2.05,f=15.843mm~17.445mm
Projection Offset:	100% +/-6%
Throw Ratio:	1.5-1.65
Image size:	30" - 300"
Throw Distance:	0.97m~10.67m(100" @3.23m)
Keystone:	±40° (Vertical)
Optical Zoom:	1.1x
Audible Noise (Normal/Eco):	31dB / 27dB
Response Time:	16ms
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

INPUT

Computer in (share with component):	1
Audio-in (3.5mm):	1
HDMI/HDCP:	2 (HDMI 1.4/ HDCP 1.4)

OUTPUT

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	2W
USB type A (Power):	1 (5V/1.5A)

CONTROL

RS232:	1
USB type mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	3.6kg
Dimensions (WxDxH) w/adjustment foot:	332x261x135mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
VGA cable:	1
Remote Control:	1
QSG:	1

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-116
--------------------	---------