

## SpectraView® Reference 302

NEC LCD 30" Colour Accurate Display

### Datasheet



**Professional 30 inch Colour Display.** The NEC SpectraView® Reference 302 is a high-end professional performance LCD monitor using latest 10-bit AH-IPS with GB-R LED backlight for colour critical applications with many features and benefits for obtaining best picture quality and colour accuracy, whilst maintaining attractive value for money.

The ideal display for all creative professionals, designers, photographers, precision engineers and anyone who cannot accept compromise on colour accuracy.

### Benefits

**Consistent Colour Viewing** - with 10-bit AH-IPS and GB-R Backlight 16:10 TFT display.

**Ergonomically Mastered** - comfortable viewing with ErgoDesign® and TORO™ design.

**Facility to create and calibrate** - thanks to the SpectraView® Profiler software, the SpectraView® certifier document and detachable black light protection hood including accessories.

**True Colours** - with a wide colour gamut (108.6 % size / 99.3 % coverage AdobeRGB) and hardware calibration with 14-bit LUT (look up table) for 42-bit colour control and gamma correction, irrespective of colour and input.

**Zero Defect Pixel Warranty** - up to 6 months after date of purchase.

**Cost Saving Device Management** save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

## Product Information

Product Name	SpectraView® Reference 302
Product Group	NEC LCD 30" Colour Accurate Display
Order Code	60003547

## Display

Panel Technology	AH-IPS GB-R LED Backlight
Screen Size [inch/cm]	29.8 / 75.6
Pixel Pitch [mm]	0.251
Brightness (typ.) [cd/m²]	340
Contrast Ratio (typ.)	1000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	12 (6 white / black; 6 black / white); 6 (grey-to-grey)
Colours [Mio.]	1074.0
Colour Gamut Size / Coverage	108.6% / 99.3% Adobe RGB

## Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 98.7 (digital)
Vertical Frequency [Hz]	50 - 85

## Resolution

Optimum Resolution	2560 x 1600 at 60 Hz
Supported	2560 x 1600; 1920 x 1440; 1920 x 1200; 1920 x 1080p; 1680 x 1050; 1600 x 1200; 1440 x 900; 1400 x 1050; 1280 x 1024; 1280 x 960; 1280 x 720p; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 576p; 720 x 480p; 640 x 480

## Connectivity

Digital	1 x DisplayPort; 1 x DVI-D; 1 x HDMI; 1 x Mini DisplayPort; USB ver. 2.0 (3 down / 2 up)
---------	--

## Electrical

Power Consumption on Mode [W]	47 (Eco Mode); 63 (typ.); 87 (max.)
Power Savings Mode [W]	1.4
Power Supply	1.1 A/0.51 A; 100-240 V; integrated power supply

## Environmental Conditions

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80

## Ergonomics

Height adjustable Stand [mm]	150 (Landscape mode)
Screen Tilt / Swivel [°]	5 to 30; -45 to +45
Screen Rotate [°]	0 to 90 (landscape to portrait mode)

## Mechanical

Bezel Width [mm]	22 (top and bottom); 22.4 (left and right)
Dimensions (W x H x D) [mm]	688 x 466 - 616 x 302 (Landscape mode)
Weight [kg]	18; Without stand: 10.7
VESA Mounting [mm]	100 x 100 (4 points); 200 x 100 (5 points)

## Additional Features

Special Characteristics	Adjustable power LED (colour and brightness); AmbiBright; Auto Black Level; Auto Brightness; Auto Contrast; AutoBright; Backlight Ageing Correction; CableComp with Sync Continuity Detection; Consistent colour viewing with 10-bit AH-IPS 16:10 TFT; Copy calibration; DDC/CI compatible; Digital Uniformity Control (ColorComp); Direct Brightness and Contrast; EcoModes; GammaComp (14 bit Look Up Table) and 14 bit Gamma Correction; NaViSet Administrator 2; OmniColor™: sRGB and 6-Axis-Colour-Control; Overdrive; Quick release Stand and Handle; RapidMotion; Self calibration; Self Diagnostics; SpectraView® Profiler Software; TileComp; TileMatrix; TORO™ Design; Windows 8 compatible
Colour Versions	Black Front Bezel, Black Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	DDC2B/2Bi; EDID Standard; VESA DDC/CI
Adjust Functions	Advanced User Menu; Auto Adjust; Black Level; Brightness; Colour Temperature Control; Contrast; Expansion Mode; Hotkeys; Intelligent Power Management; Language Select; Monitor Information; OmniColor™: sRGB and 6-axis-colour-control; On-Screen-Display (OSD) lock-out; Sharpness; sRGB; User Menu
Shipping Content	CD-ROM with SpectraView® Profiler Software and manual; Detachable black light protection hood including accessories; Monitor; Power Cable; Setup Guide; Signal Cable DisplayPort; SpectraView® Certifier document Signal Cable: [value1] x DVI-D
Safety and Ergonomics	C-tick; CCC; CE; EAC; FCC Class B; ISO 9241-307 (pixel failure class I); MPR II/ MPR III; PCBC/B-mark; PSB; RoHS; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA
Warranty	5 years warranty incl. backlight; Zero Defect Pixel Warranty up to 6 months after date of Purchase

## Green Features

Energy Efficiency	Annual energy consumption: 92 kWh (based on 4 operating hours per day); Carbon Footprint Meter / Carbon Savings Meter; Energy efficiency class: C
Ecological Materials	Efficient mechanical design for minimised packaging; Minimal use of harmful material
Ecological Standards	ErP compliant



This document is © 2016 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 29.07.2016