

Key Features

Extended Lifespan | Automatic Sleep Timer | Auto Power Off | Bright Images in Any Environment | Amazing Colour Accuracy



Product **Description**

The ViewSonic PA503X offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, PA503X projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColour™ technology offers a wider range of displayable colour ensuring true-to-life colour accuracy in both bright and dark environments without sacrificing image quality.



- 1. Keypad
- 2. LED indicator
- 3. Lamp cover
- 4. Security lock
- 5. Zoom/Focus 6. Front IR
- 7. Projection Lens
- 8. Audio in/out
- 9. HDMI
- 10. Dual VGA 11. VGA out
- 12. Mini USB
- 13. Video
- 14. Kensington® Lock Slot

Visit Us • www.viewsonic.com

Remote Control: QSG & CD:

Air Filter:

SPECIFICATION	
Projection system:	0.55" XGA
Native Resolution:	1024x768
DC type:	DC3
Brightness:	3600 ANSI Lumens
Contrast Ratio with SuperEco mode:	22000:1
Display Colour:	1.07 Billion Colours
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/15000
Lamp Watt:	190W
Lens:	F=2.56-2.68, f=22-24.1 mm
Projection Offset:	120%+/-5%
Throw Ratio:	1.96~2.15
Image size:	30" - 300"
Throw Distance:	1.19m-13.11m(100" @3.98m)
Keystone:	±40° (Vertical)
Optical Zoom:	1.1x
Audible Noise (Eco):	27dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz
INPUT	
Computer in (share with component):	2
Composite:	1
Audio-in (3.5mm):	1
HDMI:	1 (Back)
OUTPUT	
Monitor out:	1
Audio out (3.5mm):	1
Speaker:	2W
CONTROL	
RS232:	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.2kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
STANDARD ACCESSORY	
Power Cord:	1
VGA cable:	1

100-240V+/- 10%,

QSG: 1 / CD: NA

RSPL

USB type mini B (Services):