



PROJECTOR

# Pro8530HDL

## Key Features

"Flex-In" Design for Flexible Integration |  
Easy-Access Top Cover for easy  
maintenance | Network Management |  
PortAll®: Secure MHL/HDMI port with  
built-in Micro USB cable | Optional  
ViewSonic® HDBT dongle



## Product Description

The Pro8530HDL is the perfect solution for large venue Pro AV projection requirements, thanks to a centred lens, sealed engine and multiple adjustment features like vertical lens shift, 1.6x optical zoom, horizontal & vertical keystone, plus 4-corner adjustment. Utilising a unique "Flex-In" (Flexible Installation) design, the Pro8530HDL integrates an intuitive form with high flexibility and an easy installation process, making it the ideal installation projector. Equipped with 5,200 ANSI Lumens and Full HD resolution, the Pro8530HDL is powered by SuperColor™ and SonicExpert® to provide a professional audiovisual performance. It boasts a bilateral opening top cover, 4x HDMI (1 of which is MHL) and an intuitive PortAll® compartment to accommodate optimal HDBT solutions (an affordable way of transferring High Definition audio and video over long distance), wireless dongles, or PC stick integration for versatile application.

**Visit Us** ■ [www.viewsonic.com](http://www.viewsonic.com)

**PRODUCT SPECIFICATION**

Resolution:	1920x1080
Brightness (ANSI Lumens):	5200lm
Contrast (Max.):	5000: 1
Lamp Hour (Normal / Eco):	2000hrs / 2500hrs
Throw Ratio in Meters (Wide ~ Tele):	1.07~1.71
Lens Shift:	Yes
Optical Zoom:	1.6x
Digital Zoom:	0.8x~2.0x
Screen Size:	30"~300"
Projection Offset:	115%~130%±5%
Display Colours:	1.07 Billion Colors (30 bits per color)
Keystone:	HV
Noise min (Eco):	33 dB
Speaker:	10W Cube x2

**INPUT CONNECTIVITY**

HDMI/MHL:	1
HDMI In:	3
VGA-in:	2
Component Input:	2 (Share with VGA-in)
S-Video:	1
Composite Input:	1
Audio-in (3.5mm):	2
Audio-in (RCA pair):	1
USB Type A:	1 (Only charging)
USB Type B:	N/A
Mini USB:	1
Micro USB cable:	1 (Only charging)
Microphone in (3.5mm):	1 (Share with audio in 2)
SD Card reader:	N/A

**OUTPUT CONNECTIVITY**

VGA-out:	1
Audio-out (3.5mm):	1

**CONTROL**

RS232 (9 pin):	1
Network Mangment (LAN cable):	1
12V Power Trigger:	1
3D VESA:	1
IR Connector:	1

**DIMENSIONS AND POWER**

Dimension (WxDxH):	496.5 mm(W) x 316.24 mm(D) x 139.8 mm(H) 19.55" (W) x 12.45" (D) x 5.50" (H)
Net Weight:	6.3 kg (13.89 lb)
Power Source:	100~240Vac 50/60Hz
Power Consumption:	574W (Max.)

**SUPPLIED ACCESSORIES**

Power cord:	1
VGA cable:	1
HDMI cable:	N/A
Remote Control (with batteries):	1
Cable cover:	1
Quick Start Guide & CD:	1

**LANGUAGES**

On Screen Display:	Total 22 languages
--------------------	--------------------

**REGULATIONS**

Standard:	Mexico Energy test/Registration, EAC, TUVS Mark(Argentina), India BIS, FCC,CE EMC,CB,,CCC, ROHS, REACH, SVHC, WEEE, ErP, Mexico NOM, cTUVus, PSB, RCM, CECF
-----------	---

**WARRANTY**

\*\*Warranty offered may differ from market to market